



Data Sheet

PA ASTFÜLLER

Granules+ Sticks

1. Technical characteristics

Adhesive type:	Synthetic Polymer Based Hotmelt
Molten tack:	Medium
Brookfield viscosity:	5,000 cps @ 190°C
Ring & Ball softening point:	115°C
Open Time:	Medium

2. Colors



3. Packaging

3,3kg	Granules
10x25cm	Sticks
2,5kg 25cm	Sticks (Value Pack)

4. Suggested application temperature

160°C-215°C

5. Disclaimer

F.D.A. approved. All the constituent parts of this adhesive have been approved by the American F.D.A. under C.F.R 21.175.105 (Adhesives)

6. Storage

Store in a clean dry place at temperatures between 5 °C and 30 °C (41°F and 86°F) with boxes closed. Do not expose to direct sunlight or localised heat sources such as radiators or hot pipes.

We recommend these applicators:

Sticks

25 1001	HRA 220
25 1010	HRA Gas
25 1011	HRA Akku
25 1002	HRA 820
25 10021	HRA 305



HRA 220



HRA 820

Granules

25 1006	HRA200HT
25 1007	HB710HT
25 1015	HRATR55LCD
25 1005	HB450



HB 710 / 710 HT



HRA TR55 LCD

Granules

26 SMP54HT MR	Tankanlage
26 SMP104 MR	Tankanlage
26 SMP204 MRB	Tankanlage
WCS-SP XX	Schlauchpaket
WCS-HP PT100	Handpistole
WCS Sky-Gun	Handpistole



WCS Sky Gun

